

液压压接钳 HYDRAULIC CRIMPING TOOLS

YQ-70 快速液压钳

- 适用于输配电架空和地下电缆线钢铝端子、套管的压接。
- 采用六角型模具压接紧密、导电良好、不易脱落。
- It is applied to overhead distribution and press connection for copper terminals and sleeve of underground cable.
- Hexagonal mould is adopted to ensure tight press connection, good electric conduction and non-easy shedding.

工具参数	
应用范围 Range of application	6-70mm ²
出力 Crimping force	6ton
行程 Stroke	10mm
模具配置 Standard	公模 (母模) 8-38,60-70mm ² , 公模: 14-22,38-60,70mm ²
重量 Weight	2.5Kg
外箱包装尺寸 Packaging size	545x130x235mm
包装 Package	塑料箱 Plastic case



EP-410 快速液压钳

- 适用于电缆线铜铝端子套管的压接
- 采用六角型模具，压接紧密。
- 压接头部可以做 180 度的旋转
- It is applicable to press connection of cable copper and aluminum terminal bushing;
- Hexagonal mould is adopted to ensure tight press connection.
- Head part can rotate at 180° degrees.

工具参数	
应用范围 Range of application	35-240mm ² (铝端子 Al Terminal) 50-300mm ² (铜端子 Cu Terminal)
出力 Crimping force	12ton
行程 Stroke	30mm
模具配置 Standard	50,70,95,120,150,185,240,300mm ²
重量 Weight	6.6Kg
外箱包装尺寸 Packaging size	755x130x230mm
包装 Package	塑料箱 Plastic case



带安全系统
Safety system inside

EP-430 快速液压钳

- 适用于电缆线铜铝端子套管的压接
- 采用六角型模具，压接紧密
- 带安全系统
- It is applicable crimping cable copper and aluminum terminals.
- Hexagonal mould is adopted to ensure tight press connection.
- Safety system inside.

工具参数	
应用范围 Range of application	35-300mm ² (铝端子 Al Terminal) 50-400mm ² (铜端子 Cu Terminal)
出力 Crimping force	12ton
行程 Stroke	32mm
模具配置 Standard	50,70,95,120,150,185,240,300,400mm ²
重量 Weight	6.4Kg
外箱包装尺寸 Packaging size	755x130x230mm
包装 Package	塑料箱 Plastic case

