




ELECTRICAL SOLUTIONS

圆形预绝缘端头  
INSULATED SPADE TERMINALS



INSULATED SPADE TERMINALS



△导线截面: 0.5~1.5mm<sup>2</sup>(22-16) 最大电流: I<sub>max</sub>=19A

编号 ITEM.NO.	美制 螺栓号	螺栓口直径 d2	尺寸DIMENSION				Dφ mm	颜色 COLOR
			B mm	L mm	F mm	H mm		
RV1.25-3	#4	3.2mm	5.7	17.8	4.95	10.0	4.3	红 Red
RVS1.25-3.5	#6	3.7mm	5.7	17.8	4.95			
RVM1.25-3.5	#6	3.7mm	6.6	20.1	6.3			
RVL1.25-3.5	#6	3.7mm	8.0	21.5	7.0			
RVS1.25-4	#8	4.3mm	6.6	20.1	6.3			
RVL1.25-4	#8	4.3mm	8.0	21.5	7.0			
RV1.25-5	#10	5.3mm	8.0	21.5	7.0			
RV1.25-6	1/4	6.5mm	11.6	27.5	11.1			
RV1.25-8	5/16	8.4mm	11.6	27.5	11.1			
RV1.25-10	3/8	10.5mm	13.6	31.6	13.9			

△导线截面: 1.5~1.5mm<sup>2</sup>(16-14) 最大电流: I<sub>max</sub>=27A

编号 ITEM.NO.	美制 螺栓号	螺栓口直径 d2	尺寸DIMENSION				Dφ mm	颜色 COLOR
			B mm	L mm	F mm	H mm		
RV2-3	#4	3.2mm	6.6	17.8	4.3	10.0	4.9	蓝 blue
RVS2-3.5	#6	3.7mm	6.6	17.8	4.3			
RVM2-3.5	#6	3.7mm	6.6	21.0	7.0			
RVL2-3.5	#6	3.7mm	8.5	22.5	7.75			
RVS2-4	#8	4.3mm	6.6	21.0	7.0			
RVL2-4	#8	4.3mm	8.5	22.5	7.75			
RVS2-5	#10	5.3mm	8.5	22.5	7.75			
RVL2-5	#10	5.3mm	9.5	22.5	7.75			
RV2-6	1/4	6.5mm	12.0	27.6	11.0			
RV2-8	5/16	8.4mm	12.0	27.6	11.0			
RV2-10	3/8	10.5mm	13.6	30.2	13.9			

△导线截面: 2.5~4mm<sup>2</sup>(14~12) 最大电流: I<sub>max</sub>=37A

编号 ITEM.NO.	美制 螺栓号	螺栓口直径 d2	尺寸DIMENSION				Dφ mm	颜色 COLOR
			B mm	L mm	F mm	H mm		
RV3.5-4	#8	4.3mm	8.0	24.5	7.7	12.5	6.2	黑 black
RVS3.5-5	#10	5.3mm	8.0	24.5	7.7			
RVL3.5-5	#10	5.3mm	12.0	27.9	7.7			
RV3.5-6	1/4	6.5mm	12.0	27.9	7.7			

△导线截面: 4~6mm<sup>2</sup>(12~10) 最大电流: I<sub>max</sub>=48A

编号 ITEM.NO.	美制 螺栓号	螺栓口直径 d2	尺寸DIMENSION				Dφ mm	颜色 COLOR
			B mm	L mm	F mm	H mm		
RV5.5-3.5	#6	3.7mm	7.2	21.4	5.9	12.5	6.7	黄 yellow
RVS5.5-4	#8	4.3mm	7.2	21.5	5.9			
RVL5.5-4	#8	4.3mm	9.5	25.5	8.3			
RV5.5-5	#10	5.3mm	9.5	25.5	8.3			
RV5.5-6	1/4	6.5mm	12.0	21.5	13.0			
RV5.5-8	5/16	8.4mm	15.0	33.7	13.7			
RV5.5-10	3/8	10.5	15.0	33.7	13.7			
RV5.5-12	1/2	13.0	19.2	38.1	16.0			